


okvolight®

Technology Inside



NOBLY SERIES

➤ **ULTRA SLIM**
PANEL LUMINAIRES



GRANDE
ULTRA SLIM LED PANEL

GRANDE ULTRA SLIM LED PANEL LAY-ON MOUNTED

Products Features

Mounting Type

LAY-ON Mounted on Suspended Ceiling

Body

Electrostatic powder coated DKP Sheet

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm, 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Body Color RAL 9016 RAL 9006



Installation Details	Product Benefits	Areas Of Application
<p>LAY-ON mounting on suspended ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra slim body and side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Entrances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
<p>LxWxH: 595x595x8 mm</p>	<p>L1 x W1 = 576 x 576 mm</p>	<p>4.2 kg</p>	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
GRANDE LAY-ON MOUNTED	BRONZE	USP.NBL.0606.GRN.LYN.BNZ				3550 lm	Ra > 80	>0.92					2 Years
	TITANIUM	USP.NBL.0606.GRN.LYN.TNM				3650 lm	Ra > 85	>0.92					3 Years
	SILVER	USP.NBL.0606.GRN.LYN.SLV	2900 K	4200K	6500 K	3650 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	595x595x8 mm	2 Years
	GOLD	USP.NBL.0606.GRN.LYN.GLD				3750 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	USP.NBL.0606.GRN.LYN.PLT				3850 lm	Ra > 85	>0.95					3 Years

For more information on other models, www.okvolight.com

GRANDE ULTRA SLIM LED PANEL CLIP-IN MOUNTED

Products Features

Mounting Type

CLIP-IN Mounted on Suspended Ceiling

Body

Electrostatic powder coated DKP Sheet

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm, 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Installation Details	Product Benefits	Areas Of Application
<p>CLIP-IN mounting on suspended ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra slim body and side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Enterances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
<p>LxWxH: 600x600x25 mm</p>	<p>L1 x W1 = 600 x 600 mm</p>	<p>4.4 kg</p>	

Product Series	Product Model	Product Code	Color Temperature	Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
GRANDE CLIP-IN MOUNTED	BRONZE	USP.NBL.0606.GRN.CLIP.BNZ		3550 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	600x600x25 mm	2 Years
	TITANIUM	USP.NBL.0606.GRN.CLIP.TNM		3650 lm	Ra > 85	>0.92					3 Years
	SILVER	USP.NBL.0606.GRN.CLIP.SLV	2900 K 4200K 6500 K	3650 lm	Ra > 80	>0.92					2 Years
	GOLD	USP.NBL.0606.GRN.CLIP.GLD		3750 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	USP.NBL.0606.GRN.CLIP.PLT		3850 lm	Ra > 85	>0.95					3 Years

For more information on other models, www.okvilight.com

GRANDE ULTRA SLIM LED PANEL FLUSH MOUNTED

Products Features

Mounting Type

FLUSH Mounted on Suspended Ceiling

Body

Electrostatic powder coated DKP Sheet

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm, 600x1200 mm


Optional & Additional Features




- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Body Color RAL 9016 RAL 9006



Installation Details	Product Benefits	Areas Of Application
 <p>FLUSH mounting on suspended ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra slim body and side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation. ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Entrances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
 <p>LxWxH: 595x595x8 mm</p>	 <p>L1 x W1 = 565x 565 mm</p>	 <p>4.3 kg</p>	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
GRANDE FLUSH MOUNTED	BRONZE	USP.NBL.0606.GRN.FL.H.BNZ				3550 lm	Ra> 80	>0.92					2 Years
	TITANIUM	USP.NBL.0606.GRN.FL.H.TNM				3650 lm	Ra> 85	>0.92					3 Years
	SILVER	USP.NBL.0606.GRN.FL.H.SLV	2900 K	4200K	6500 K	3650 lm	Ra> 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	595x595x8 mm	2 Years
	GOLD	USP.NBL.0606.GRN.FL.H.GLD				3750 lm	Ra> 85	>0.92					3 Years
	PLATINIUM	USP.NBL.0606.GRN.FL.H.PLT				3850 lm	Ra> 85	>0.95					3 Years

For more information on other models, www.okvolight.com

GRANDE ULTRA SLIM LED PANEL SURFACE MOUNTED

Products Features

Mounting Type

SURFACE Mounted on Ceiling

Body

Electrostatic powder coated DKP Sheet

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature


-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm , 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Body Color RAL 9016 RAL 9006



Installation Details	Product Benefits	Areas Of Application
<p>SURFACE mounting on ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra slim body and side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Enterances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
<p>LxWxH: 595x595x50 mm</p>	<p>L1 x W1 = 535 x 375 mm</p>	<p>5.0 kg</p>	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
GRANDE SURFACE MOUNTED	BRONZE	USP.NBL.0606.GRN.SFC.BNZ				3550 lm	Ra > 80	>0.92					2 Years
	TITANIUM	USP.NBL.0606.GRN.SFC.TNM				3650 lm	Ra > 85	>0.92					3 Years
	SILVER	USP.NBL.0606.GRN.SFC.SLV	2900 K	4200K	6500 K	3650 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	595x595x50 mm	2 Years
	GOLD	USP.NBL.0606.GRN.SFC.GLD				3750 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	USP.NBL.0606.GRN.SFC.PLT				3850 lm	Ra > 85	>0.95					3 Years

For more information on other models, www.okvilight.com



INFANTE

ULTRA SLIM LED PANEL

INFANTE ULTRA SLIM LED PANEL LAY-ON MOUNTED

Products Features

Mounting Type

LAY-ON Mounted on Suspended Ceiling

Body

Electrostatic powder coated Aluminum

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm , 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Installation Details	Product Benefits	Areas Of Application
<p>LAY-ON mounting on suspended ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra Slim and lightweight aluminum body, side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Enterances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
<p>LxWxH: 595x595x7.4 mm</p>	<p>L1 x W1 = 576 x 576 mm</p>	<p>3.5 kg</p>	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
INFANTE LAY-ON MOUNTED	BRONZE	ASP.NBL.0606.INF.LYN.BNZ				3500 lm	Ra > 80	>0.92					2 Years
	TITANIUM	ASP.NBL.0606.INF.LYN.TNM				3600 lm	Ra > 85	>0.92					3 Years
	SILVER	ASP.NBL.0606.INF.LYN.SLV	2900 K	4200K	6500 K	3600 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	595x595x7,4mm	2 Years
	GOLD	ASP.NBL.0606.INF.LYN.GLD				3700 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	ASP.NBL.0606.INF.LYN.PLT				3800 lm	Ra > 85	>0.95					3 Years

INFANTE ULTRA SLIM LED PANEL CLIP-IN MOUNTED

Products Features

Mounting Type

CLIP-IN Mounted on Suspended Ceiling

Body

Electrostatic powder coated Aluminum

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm, 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1 -3 hours)
- ▶ OKVO Smart Applications



Body Color RAL 9016 RAL 9006



Installation Details	Product Benefits	Areas Of Application
<p>CLIP-IN mounting on suspended ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra Slim and lightweight aluminum body, side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Entrances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams																																																		
<p>LxWxH: 600x600x25mm</p>	<p>L1 x W1 = 600 x 600 mm</p>	<p>3.7 kg</p>	<p>Beam spread table:</p> <table border="1"> <thead> <tr> <th>Beam Angle (°)</th> <th>Beam Diameter (m)</th> <th>Beam Area (m²)</th> <th>Beam Length (m)</th> <th>Beam Volume (m³)</th> </tr> </thead> <tbody> <tr><td>1.4</td><td>1.43</td><td>2.04</td><td>1.43</td><td>2.92</td></tr> <tr><td>1.6</td><td>1.60</td><td>2.51</td><td>1.60</td><td>4.02</td></tr> <tr><td>1.8</td><td>1.80</td><td>3.24</td><td>1.80</td><td>5.40</td></tr> <tr><td>2.0</td><td>2.00</td><td>4.00</td><td>2.00</td><td>8.00</td></tr> <tr><td>2.2</td><td>2.24</td><td>5.01</td><td>2.24</td><td>10.08</td></tr> <tr><td>2.4</td><td>2.40</td><td>5.76</td><td>2.40</td><td>11.52</td></tr> <tr><td>2.6</td><td>2.60</td><td>6.76</td><td>2.60</td><td>13.52</td></tr> <tr><td>2.8</td><td>2.80</td><td>7.84</td><td>2.80</td><td>15.68</td></tr> <tr><td>3.0</td><td>3.00</td><td>9.00</td><td>3.00</td><td>18.00</td></tr> </tbody> </table>	Beam Angle (°)	Beam Diameter (m)	Beam Area (m²)	Beam Length (m)	Beam Volume (m³)	1.4	1.43	2.04	1.43	2.92	1.6	1.60	2.51	1.60	4.02	1.8	1.80	3.24	1.80	5.40	2.0	2.00	4.00	2.00	8.00	2.2	2.24	5.01	2.24	10.08	2.4	2.40	5.76	2.40	11.52	2.6	2.60	6.76	2.60	13.52	2.8	2.80	7.84	2.80	15.68	3.0	3.00	9.00	3.00	18.00
Beam Angle (°)	Beam Diameter (m)	Beam Area (m²)	Beam Length (m)	Beam Volume (m³)																																																	
1.4	1.43	2.04	1.43	2.92																																																	
1.6	1.60	2.51	1.60	4.02																																																	
1.8	1.80	3.24	1.80	5.40																																																	
2.0	2.00	4.00	2.00	8.00																																																	
2.2	2.24	5.01	2.24	10.08																																																	
2.4	2.40	5.76	2.40	11.52																																																	
2.6	2.60	6.76	2.60	13.52																																																	
2.8	2.80	7.84	2.80	15.68																																																	
3.0	3.00	9.00	3.00	18.00																																																	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
INFANTE CLIP-IN MOUNTED	BRONZE	ASP.NBL.0606.INF.CLIP.BNZ				3500 lm	Ra > 80	>0.92					2 Years
	TITANIUM	ASP.NBL.0606.INF.CLIP.TNM				3600 lm	Ra > 85	>0.92					3 Years
	SILVER	ASP.NBL.0606.INF.CLIP.SLV	2900 K	4200K	6500 K	3600 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	600x600x25mm	2 Years
	GOLD	ASP.NBL.0606.INF.CLIP.GLD				3700 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	ASP.NBL.0606.INF.CLIP.PLT				3800 lm	Ra > 85	>0.95					3 Years

For more information on other models, www.okvolight.com

INFANTE ULTRA SLIM LED PANEL FLUSH MOUNTED

Products Features

Mounting Type

FLUSH Mounted on Suspended Ceiling

Body

Electrostatic powder coated Aluminum

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm , 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Installation Details	Product Benefits	Areas Of Application
<p>FLUSH mounting on suspended ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra Slim and lightweight aluminum body, side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Enterances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
<p>LxWxH: 595x595x7.4 mm</p>	<p>L1 x W1 = 565 x 565 mm</p>	<p>3,6 kg</p>	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
INFANTE FLUSH MOUNTED	BRONZE	ASP.NBL.0606.INF.FLH.BNZ				3500 lm	Ra > 80	>0.92					2 Years
	TITANIUM	ASP.NBL.0606.INF.FLH.TNM				3600 lm	Ra > 85	>0.92					3 Years
	SILVER	ASP.NBL.0606.INF.FLH.SLV	2900 K	4200K	6500 K	3600 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	595x595x 7,4mm	2 Years
	GOLD	ASP.NBL.0606.INF.FLH.GLD				3700 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	ASP.NBL.0606.INF.FLH.PLT				3800 lm	Ra > 85	>0.95					3 Years

INFANTE ULTRA SLIM LED PANEL SURFACE MOUNTED

Products Features

Mounting Type

SURFACE Mounted on Ceiling

Body

Electrostatic powder coated Aluminum

Diffuser

Opal diffuser with prismatic surface, providing homogeneous light

LED

≥50,000 h lifetime, high efficiency and high color quality index.

Color Temperature

Cool White, Natural White, Warm White

Driver

Constant current LED driver with high efficiency,

Operating Temperature

-25 ° C / + 50 ° C operating ambient temperature range

Dimension Alternatives

600x600 mm, 300x300 mm, 300x600 mm, 300x1200 mm, 600x1200 mm

Optional & Additional Features

- ▶ DALI Driver Compatible
- ▶ Dimmable with DIMM Moduls
- ▶ Emergency Lighting Kit (1-3 hours)
- ▶ OKVO Smart Applications



Installation Details	Product Benefits	Areas Of Application
<p>SURFACE mounting on ceiling</p>	<ul style="list-style-type: none"> ▶ Ultra Slim and lightweight aluminum body, side-light design. ▶ Energy savings of up to 50 % compared to conventional luminaires ▶ High luminous efficiency, very homogeneous light ▶ No IR or UV radiation ▶ Long lifetime and low maintenance costs ▶ Easy and quick installation, ▶ Compatible with the latest lighting control technology. 	<ul style="list-style-type: none"> ▶ Offices, Corridors, Meeting Rooms, ▶ Schools, Hotels and Hospitals, ▶ Retails and Shopping Centers, ▶ Conference and Ballrooms, ▶ Entrances and Livingrooms, ▶ Modular Constructions

Dimensions	Mounting Hole Sizes	Weight	Photometric Diagrams
<p>LxWxH: 595x595x50 mm</p>	<p>L1 x W1 = 535 x 375 mm</p>	<p>4.3 kg</p>	

Product Series	Product Model	Product Code	Color Temperature			Lumen	CRI	PFC(λ)	Power	Voltage	Lifetime	Dimensions	Warranty
INFANTE SURFACE MOUNTED	BRONZE	ASP.NBL.0606.INF.SFC.BNZ				3500 lm	Ra > 80	>0.92					2 Years
	TITANIUM	ASP.NBL.0606.INF.SFC.TNM				3600 lm	Ra > 85	>0.92					3 Years
	SILVER	ASP.NBL.0606.INF.SFC.SLV	2900 K	4200K	6500 K	3600 lm	Ra > 80	>0.92	38 W	220-240 V @50-60 Hz	50.000 h	595x595x50 mm	2 Years
	GOLD	ASP.NBL.0606.INF.SFC.GLD				3700 lm	Ra > 85	>0.92					3 Years
	PLATINIUM	ASP.NBL.0606.INF.SFC.PLT				3800 lm	Ra > 85	>0.95					3 Years

For more information on other models, www.okvolight.com

okvolight®

Mimarsinan Organize Sanayi Bölgesi
Kastim Cad. No:22/B Kayseri / TURKEY
T : +90 352 228 00 28
F : +90 352 228 00 29
www.okvolight.com

© 2018, Okvolight. All rights reserved.

We reserve the right to change specifications, product descriptions, product quality, pricing and application at any time without prior written or oral notice.